

CMU/Cast-in-Place Concrete Wall Construction

Apply a thick bead of **FastFlash** or **Joint & Seam Filler** in each corner and in a zigzag pattern over the inside the concrete block rough opening. Use a dry spatula, trowel or chipper brush to spread the wet product to protect the rough opening CMU surface. Apply additional **FastFlash** or **Joint & Seam Filler** as needed to create an opaque, monolithic flashing membrane free of voids or pinholes. Allow membrane to skin over.

If wood bucks are not already installed, apply two (2) thick beads of **FastFlash** or **Joint & Seam Filler** along the perimeter faces of the wood bucks before attaching to the structure while still wet. Install anchor bolts to secure the wood bucks into the opening. Tapcons/anchor holes should be pre-drilled and blown out with oil-free air in preparation to receive a shot of **FastFlash** or **Joint & Seam Filler** into the hole prior to inserting tapcon/anchor.

After installation of wood buck, spot and cover the installed head of the anchor bolts.

Apply a thick bead of **FastFlash** or **Joint & Seam Filler** to the perimeter joint between the wood buck and CMU wall. Use a dry spatula or trowel to seal the joint. Create a profile that directs bulk water away from the joint. Allow **FastFlash** or **Joint & Seam Filler** to skim over. Apply **FastFlash** over the inside of the wood buck, extending the membrane out to the edge of the return opening when used for window protection only. When used in conjunction w/an entire air/moisture barrier system, carry the **FastFlash** out on to the face of the vertical wall 4-6 inches to facilitate a tie in to an air barrier system.

